



Lightwave 3+ Colour Touch

WPA Spectrophotometers

The Lightwave 3+ Colour Touch is truly an all-encompassing UV/Visible Spectrophotometer.

Originally designed for water analysis, the Lightwave spectrophotometers are now used in laboratories around the world for life sciences and chemical analysis as well as rigorous industrial and environmental quality control and monitoring applications.

Now with a colour touch screen control panel, this compact and robust instrument is perfect for the most demanding laboratories.

Features & Benefits

- Wavelength Range: 190 to 1100 nm
- Fast and easy to use wavelength scanning, kinetics, single or multiple wavelength reading, standard curve and absorbance ratio capability
- 5 inch colour touch screen with zoom and track function
- Accepts up to 40 mm pathlength cuvette for sensitivity in analysis of dilute solutions
- 2 year warranty

Technical Specifications

Technical	
Wavelength Range	190 to 1100 nm
Monochromator	Flat grating
Wavelength Calibration	Automatic upon switch on
Beam Height	15 mm
Spectral Bandwidth	5 nm or 3 nm for '+' models
Wavelength Accuracy	±2 nm
Wavelength Reproducibility	±1 nm
Light Sources	Xenon flash lamp
Detector	Twin CMOS array
Photometric Range	-0.300 to 2.500 A, 0.3 to 199 %T
Photometric Linearity	±1.3 % or ±0.008 A whichever is greater at 546 nm
Photometric Reproducibility	±0.002 A to 0.5 A at 546 nm
Stray Light	<0.5 %T 340 nm
Stability	±0.01 A/h at 340 nm
Noise	±0.005 peak to peak ±0.002 RMS

Technical Specifications

Software	
Applications	Single wavelength Multi wavelength Concentration Standard curve Wavelength scanning Kinetics Absorbance ratio
Digital Output	USB flash drive, PC via PVC software, Optional: Wireless
Data Export	USB flash drive: .tsv, native PVC format PC via PVC: .csv, .emf, .xlsx, .xls, .rtf, .tsv, native PVC format
Method Storage	90 with PIN number protection
Graphical Display	Yes, zoom and track function
Sample ID	Yes
Languages	English, German, French, Spanish, Italian, Japanese, Chinese
Dimensions	260 × 390 × 100 mm
Weight	3.00 kg

Ordering Info

Order #	Product
80-3007-67	WPA Lightwave 3+ CT
80-3007-68	WPA Lightwave 3+ CT with Printer
80-3007-69	WPA Lightwave 3+ CT Wireless
80-3007-70	WPA Lightwave 3+ CT Wireless with Printer



Biochrom Ltd.
Unit 7, Enterprise Zone 3970
Cambridge Research Park,
Cambridge, CB25 9PE, UK

Sales: sales@biochrom-us.com

Technical Support:
enquiries@biochrom.co.uk

Web: www.biochrom.co.uk

United Kingdom:
Tel: +44 (0) 1223 423 7233

Americas:
Tel: +1 800 272 2775